

S14M-pitch timing belts have a 14mm curvilinear tooth pitch. They are used in heavy drives. We make our S14M-pitch timing belts with a thermoset rubber reinforced with fiberglass.

The Super High Torque S14M tooth profile is designed to engage the pulley better than a traditional 14M high torque profile. This distributes belt force more evenly across the tooth. The result is improved horsepower capacity, lower tooth shear, quieter running, and longer life. For the best performance however, use one of the following belt designs:

Goodyear BlackHawk Pd™ (improvement on RPP Panther and QT Power Chain®),

Goodyear Falcon Pd™ (improvement on Gates PolyChain® GT®2),

Goodyear's Eagle Pd™ helical offset tooth (the most advanced belt design today).

Style	Teeth	Length	Style	Teeth	Length
1008-S14M	72	1008	2450-S14M	175	2450
1120-S14M	80	1120	2506-S14M	179	2506
1190-S14M	85	1190	2590-S14M	185	2590
1246-S14M	89	1246	2660-S14M	190	2660
1400-S14M	100	1400	2800-S14M	200	2800
1540-S14M	110	1540	3150-S14M	225	3150
1610-S14M	115	1610	3500-S14M	250	3500
1652-S14M	118	1652	3556-S14M	254	3556
1778-S14M	127	1778	3850-S14M	275	3850
1806-S14M	129	1806	4004-S14M	286	4004
1890-S14M	135	1890	4060-S14M	290	4060
1904-S14M	136	1904	4326-S14M	309	4326
2002-S14M	143	2002	4508-S14M	322	4508
2100-S14M	150	2100	5012-S14M	358	5012
2240-S14M	160	2240			
2310-S14M	165	2310			
2380-S14M	170	2380			

Copyright 2005
 New England Belting Company LLC
 30 Holmes Road
 Newington, CT 06111

Tel: 800-235-8126
Info@newenglandbelting.com