

S3M-pitch timing belts have a 3mm curvilinear tooth pitch. These belts are predominately found in business machines, small appliances and the like, where small gears need to be driven within a compact space.

The Super High Torque S3M tooth profile is designed to engage the pulley better than a traditional 3M high torque profile. This distributes belt force more evenly across the tooth. The result is improved horsepower capacity, lower tooth shear, quieter running, and longer life.

We make our S3M-pitch timing belts with a thermoset rubber reinforced with fiberglass.

Style	Teeth Length		Style	Teeth Length		Style	Teeth Length	
123-S3M	41	123	249-S3M	83	249	363-S3M	121	363
129-S3M	43	129	252-S3M	84	252	366-S3M	122	366
144-S3M	48	144	255-S3M	85	255	372-S3M	124	372
150-S3M	50	150	258-S3M	86	258	378-S3M	126	378
159-S3M	53	159	264-S3M	88	264	384-S3M	128	384
162-S3M	54	162	267-S3M	89	267	387-S3M	129	387
168-S3M	56	168	270-S3M	90	270	390-S3M	130	390
171-S3M	57	171	273-S3M	91	273	399-S3M	133	399
174-S3M	58	174	276-S3M	92	276	402-S3M	134	402
177-S3M	59	177	279-S3M	93	279	405-S3M	135	405
180-S3M	60	180	282-S3M	94	282	408-S3M	136	408
186-S3M	62	186	285-S3M	95	285	417-S3M	139	417
189-S3M	63	189	288-S3M	96	288	420-S3M	140	420
192-S3M	64	192	291-S3M	97	291	423-S3M	141	423
195-S3M	65	195	297-S3M	99	297	426-S3M	142	426
201-S3M	67	201	300-S3M	100	300	432-S3M	144	432
204-S3M	68	204	303-S3M	101	303	438-S3M	146	438
207-S3M	69	207	309-S3M	103	309	444-S3M	148	444
210-S3M	70	210	312-S3M	104	312	447-S3M	149	447
213-S3M	71	213	315-S3M	105	315	453-S3M	151	453
219-S3M	73	219	318-S3M	106	318	459-S3M	153	459
222-S3M	74	222	324-S3M	108	324	468-S3M	156	468
225-S3M	75	225	327-S3M	109	327	471-S3M	157	471
228-S3M	76	228	330-S3M	110	330	480-S3M	160	480
234-S3M	78	234	339-S3M	113	339	486-S3M	162	486
237-S3M	79	237	342-S3M	114	342	489-S3M	163	489
240-S3M	80	240	351-S3M	117	351	492-S3M	164	492
243-S3M	81	243	354-S3M	118	354	498-S3M	166	498
246-S3M	82	246	360-S3M	120	360	501-S3M	167	501

Style	Teeth	Length	Style	Teeth	Length
507-S3M	169	507	735-S3M	245	735
516-S3M	172	516	741-S3M	247	741
519-S3M	173	519	750-S3M	250	750
522-S3M	174	522	768-S3M	256	768
525-S3M	175	525	771-S3M	257	771
534-S3M	178	534	789-S3M	263	789
537-S3M	179	537	804-S3M	268	804
540-S3M	180	540	810-S3M	270	810
549-S3M	183	549	825-S3M	275	825
552-S3M	184	552	852-S3M	284	852
555-S3M	185	555	882-S3M	294	882
564-S3M	188	564	885-S3M	295	885
573-S3M	191	573	888-S3M	296	888
579-S3M	193	579	900-S3M	300	900
588-S3M	196	588	918-S3M	306	918
597-S3M	199	597	927-S3M	309	927
600-S3M	200	600	936-S3M	312	936
609-S3M	203	609	990-S3M	330	990
621-S3M	207	621	1119-S3M	373	1119
633-S3M	211	633	1146-S3M	382	1146
648-S3M	216	648	1188-S3M	396	1188
651-S3M	217	651	1299-S3M	433	1299
657-S3M	219	657	1530-S3M	510	1530
660-S3M	220	660	2082-S3M	694	2082
666-S3M	222	666			
681-S3M	227	681			
690-S3M	230	690			
699-S3M	233	699			
726-S3M	242	726			

Copyright 2005
New England Belting Company LLC
30 Holmes Road
Newington, CT 06111

Tel: 800-235-8126
Info@newenglandbelting.com