

S4.5M-pitch timing belts have a 4.5mm curvilinear tooth pitch. These belts are predominately found in business machines, small appliances and the like, where small gears need to be driven within a compact space.

The Super High Torque S4.5M tooth profile is designed to engage the pulley better than a traditional high torque profile. This distributes belt force more evenly across the tooth. The result is improved horsepower capacity, lower tooth shear, quieter running, and longer life.

We make our S4.5M-pitch timing belts with a thermoset rubber reinforced with fiberglass.

<b>Style</b>	<b>Teeth</b>	<b>Length</b>	<b>Style</b>	<b>Teeth</b>	<b>Length</b>
162-S4.5M	36	162	450-S4.5M	100	450
180-S4.5M	40	180	491-S4.5M	109	491
198-S4.5M	44	198	500-S4.5M	111	500
225-S4.5M	50	225	504-S4.5M	112	504
239-S4.5M	53	239	518-S4.5M	115	518
247-S4.5M	55	247	558-S4.5M	124	558
252-S4.5M	56	252	563-S4.5M	125	563
279-S4.5M	62	279	612-S4.5M	136	612
284-S4.5M	63	284	621-S4.5M	138	621
297-S4.5M	66	297	630-S4.5M	140	630
306-S4.5M	68	306	653-S4.5M	145	653
315-S4.5M	70	315	711-S4.5M	158	711
324-S4.5M	72	324	729-S4.5M	162	729
333-S4.5M	74	333	801-S4.5M	178	801
342-S4.5M	76	342	864-S4.5M	192	864
351-S4.5M	78	351	905-S4.5M	201	905
369-S4.5M	82	369	1031-S4.5M	229	1031
383-S4.5M	85	383			
387-S4.5M	86	387			
396-S4.5M	88	396			

Copyright 2005  
 New England Belting Company LLC  
 30 Holmes Road  
 Newington, CT 06111

Tel: 800-235-8126  
[Info@newenglandbelting.com](mailto:Info@newenglandbelting.com)