

S5M-pitch timing belts have a 5mm curvilinear tooth pitch. They are used in small to medium drives.

The Super High Torque S5M tooth profile is designed to engage the pulley better than a traditional 5M high torque profile. This distributes belt force more evenly across the tooth. The result is improved horsepower capacity, lower tooth shear, quieter running, and longer life.

We make our S5M-pitch timing belts with a thermoset rubber reinforced with fiberglass.

Style	Teeth Length		Style	Teeth Length		Style	Teeth Length	
225-S5M	45	225	565-S5M	113	565	870-S5M	174	870
255-S5M	51	255	575-S5M	115	575	900-S5M	180	900
275-S5M	55	275	590-S5M	118	590	920-S5M	184	920
295-S5M	59	295	600-S5M	120	600	940-S5M	188	940
320-S5M	64	320	625-S5M	125	625	950-S5M	190	950
325-S5M	65	325	635-S5M	127	635	965-S5M	193	965
350-S5M	70	350	645-S5M	129	645	975-S5M	195	975
375-S5M	75	375	650-S5M	130	650	1000-S5M	200	1000
380-S5M	76	380	665-S5M	133	665	1025-S5M	205	1025
390-S5M	78	390	670-S5M	134	670	1050-S5M	210	1050
400-S5M	80	400	675-S5M	135	675	1125-S5M	225	1125
410-S5M	82	410	695-S5M	139	695	1135-S5M	227	1135
420-S5M	84	420	700-S5M	140	700	1145-S5M	229	1145
425-S5M	85	425	710-S5M	142	710	1195-S5M	239	1195
435-S5M	87	435	725-S5M	145	725	1225-S5M	245	1225
440-S5M	88	440	740-S5M	148	740	1250-S5M	250	1250
445-S5M	89	445	750-S5M	150	750	1260-S5M	252	1260
450-S5M	90	450	765-S5M	153	765	1270-S5M	254	1270
475-S5M	95	475	770-S5M	154	770	1295-S5M	259	1295
490-S5M	98	490	775-S5M	155	775	1350-S5M	270	1350
500-S5M	100	500	800-S5M	160	800	1420-S5M	284	1420
520-S5M	104	520	810-S5M	162	810	1595-S5M	319	1595
525-S5M	105	525	830-S5M	166	830	1800-S5M	360	1800
550-S5M	110	550	850-S5M	170	850	2000-S5M	400	2000
560-S5M	112	560	860-S5M	172	860	2770-S5M	554	2770

Copyright 2005
 New England Belting Company LLC
 30 Holmes Road
 Newington, CT 06111

Tel: 800-235-8126
Info@newenglandbelting.com